



BASK仕様

巾：8mm±0.1mm

用途	メーカー	品種	厚さ(mm)/交差		長さ(m)	備考
パンチングキャリア用	東京製紙(株)	BASK42T-4200M	0.420	±0.020	4,200	
		BASK42T-6600M	0.420	±0.020	6,600	
		BASK58T-3200M	0.580	±0.020	3,200	
		BASK60T-3200M	0.600	±0.020	3,200	
		BASK60T-5000M	0.600	±0.020	5,000	
		BASK75T-4200M	0.750	±0.030	4,200	
	日本製紙クレシア(株)	BASK95TD-3000M	0.950	±0.030	3,000	
		BASK40K-4200M	0.400	±0.020	4,200	
		BASK60K-3200M	0.600	±0.020	3,200	
	BASK68K-3000M	0.680	±0.020	3,000		
プレスキャリア用途	東京製紙(株)	BASK31T-4200M	0.310	±0.020	4,200	0402用
		BASK42T-3200M	0.610	±0.020	3,200	0603用
		BASK61T-3200M	0.610	±0.020	3,200	
		BASK65T-3000M	0.650	±0.020	3,000	
		BASK75T-4200M	0.750	±0.030	4,200	
	日本製紙クレシア(株)	MPC31-4200M	0.310	±0.020	4,200	0402用
	MPC42-3500M	0.420	±0.020	3,500	0603用	
特殊用途	東京製紙(株)	BASK31TAG-4200M	0.310	±0.020	4,200	
	日本製紙クレシア(株)	BASK15KAG-4200M	0.150	±0.020	4,200	
		BASK20KAG-4200M	0.200	±0.020	4,200	
	BASK31KAG-4200M	0.310	±0.020	4,200		


※上記は一例です

プレスキャリアテープ仕様

巾：8mm±0.1mm

用途	A/交差(mm)		B/交差(mm)		P1/交差(mm)		P0/交差(mm)		K'/交差(mm)		T/交差(mm)		備考
0402R	0.260	±0.020	0.460	±0.020	2.000	±0.050	4.000	±0.100	0.15-0.17	±0.020	0.310	±0.020	
0402C	0.250	±0.020	0.450	±0.020	2.000	±0.050	4.000	±0.100	0.23-0.25	±0.020	0.310	±0.020	
0603R	0.380	±0.020	0.680	±0.020	2.000	±0.050	4.000	±0.100	0.26-0.28	±0.020	0.420	±0.020	
0603C	0.360	±0.020	0.660	±0.020	2.000	±0.050	4.000	±0.100	0.36-0.38	±0.020	0.420	±0.020	

※上記は一例です



パンチキャリアテープ仕様

巾：8mm±0.1mm

用途	A/交差(mm)		B/交差(mm)		P1/交差(mm)		P0/交差(mm)		T/交差(mm)		備考
1005	0.620	±0.030	1.120	±0.030	2.000	±0.050	4.000	±0.100	0.400	±0.030	
1005	0.650	±0.030	1.150	±0.030	2.000	±0.050	4.000	±0.100	0.600	±0.030	
1608	1.020	±0.050	1.820	±0.050	2.000	±0.050	4.000	±0.100	0.600	±0.030	
1608	1.050	±0.050	1.850	±0.050	4.000	±0.100	4.000	±0.100	0.750	±0.050	
2012	1.600	±0.050	2.350	±0.050	4.000	±0.100	4.000	±0.100	0.950	±0.050	
3216	2.000	±0.050	3.500	±0.050	4.000	±0.100	4.000	±0.100	0.950	±0.050	

※上記は一例です

※仕様は予告なく変更となる場合があります